

## PRODUCT SPECIFICATIONS

MANUFACTURER VIDRIERA DEL CARDONER, S.A.

- DESCRIPTION

Clear translucent glass with design.

# BRILLAMAT®

- USE

Doors, partitions, mobiliario, bath bulkheads, handrails, façades, rooflights, etc.

## TECHNICAL SPECIFICATIONS

### GLASS CHARACTERISTICS

- TYPE OF GLASS

Clear float glass basis according UNE-EN 572-2 regulation and CE certification.

- SIZES

3210x2250mm.

- THICKNESSES

4, 5, 6, 8 & 10 mm.

- COLOR

Basis float glass is clear. On demand they can be produced on colored float glasses or low iron.

- CLEANING

This glass offers exceptional easy to clean conditions due to its particular acid treatment.

### PRODUCTION CONDITIONS

- PROCESSING

Float glass treated on its surface with an acid composition  
In order to obtain a fine translucent-satin finish with design.  
No alteration of its mechanical features.

- ALLOWED SECURITY TREATMENTS

Can be tempered by the standards of the norm EN 12150 for tempered glass.

Can be laminated for the not treated side according to the standards of the norm EN 12543 for laminated glass.

- EDGE TOLERANCE

15 mm maximum on the 3210 mm side and 5 mm on the 2250 mm side as a result of the manufacturing process.

- LIGHT AND ENERGETIC CHARACTERISTICS

Depending on the color, the design, the thickness of glass and the placing the treated side, position 1 or 2.

## RECOMMENDATIONS

### STORAGE

Store the product in a dry place. If moisture/humidity is detected, separate the sheets and dry immediately.

### MANUFACTURE

Cutting for the untreated side, regular manufacture, with neutral PH cooling liquid and immediate wash and dry.

### WASHING

With neutral PH detergent, and immediate dry.

### USE OF SILICONE

Use only neutral PH silicone (non-acid).

## RESPONSIBILITY

Vidriera del Cardoner, S.A. is not responsible for any other value than the product supplied, and replace by another the whole sheet that is the subject of complaint.