

PRODUCT SPECIFICATIONS

NOVOMAT®

MANUFACTURER VIDRIERA DEL CARDONER, S.A.

- DESCRIPTION
Translucent clear float glass with satin look obtained through a chemical process.
- USE
Doors, partitions, mobiliario, work tables, worktops, bath blukheds, bathrooms and kitchen's countertops, handrails, rooflights, etc.

TECHNICAL SPECIFICATIONS

GLASS CHARACTERISTICS

- TYPE OF GLASS
Clear float glass basis according UNE-EN 572-2 regulation and CE certification.
- SIZES
3210x2250mm.
- THICKNESSES
4, 5, 6, 8,10 & 12 mm.
- COLOR
Basis float glass is clear. On demand can be produced on color basis float glass.
- CLEANING
This glass offers exceptional easy to clean conditions due to its particular acid treatment.

PRODUCTION CONDITIONS

- PROCESSING
Float glass treated on its surface with an acid composition In order to obtain a fine translucent-satin finish. No alteration of its mechanical features.
- ALLOWED SECURITY TREATMENTS
Can be tempered by the standards of the norm EN 12150 for tempered glass.

Can be laminated for the not treated side according to the standards of the norm EN 12543 for laminated glass.
- EDGE TOLERANCE
15 mm maximum on the 3210 mm side and 5mm on the 2250mm side as a result of the manufacturing process.
- LIGHT AND ENERGETIC CHARACTERISTICS
Depending on the color, the design, the thickness of glass and the placing the treated side, position 1 or 2.

RECOMMENDATIONS

STORAGE

Store the product in a dry place. If moisture/humidity is detected, separate the sheets and dry immediately.

MANUFACTURE

Cutting for the untreated side, regular manufacture, with neutral PH cooling liquid and immediate wash and dry.

WASHING

With neutral PH detergent, and immediate dry.

USE OF SILICONE

Use only neutral PH silicone (non-acid).

RESPONSIBILITY

Vidriera del Cardoner, S.A. is not responsible for any other value than the product supplied, and replace by another the whole sheet that is the subject of complaint.